

## PARLA Outlet products

### Quality

The boards may have one or more of the following defects:

- Minor surface treatment defects
- Hairline cracks, filled cracks, and minor cracking
- Height differences in the longitudinal and lateral direction of the board  $> \pm 0.2$  mm
- Bending of the board
- Filling of knots
- Cracking of knots and filling defects
- Dents, scratches, and other minor damage
- Higher than normal colour variation

Individual defects may be deviations from the normal quality standard, or technical defects that can be eliminated by cutting.

### Installation of outlet-quality boards

In addition to normal installation instructions, the following is to be observed:

- After the installation, check the result and, if necessary, fill any cracks and holes with a wood putty of suitable colour. In the case of oiled products, apply a small amount of wax oil to the repaired spots.
- Defects in boards can be repaired during installation by removing or filling the defective spot.
- If the defect is located at the end of the board, the defective section can be cut off and the board can be used at the end or beginning of a row.
- During installation, you should have 2–3 packages of boards open at the same time, so that the boards with the most obvious defects can be cut or installed in places where they are less visible.

### Warranty

**The manufacturer does not provide a warranty for the Outlet products.**

**When it comes to the products' ability to stay fastened, Outlet products are provided with the same 10-year warranty as A-grade products, provided that the installation instructions for Outlet products have been followed.**

**[www.parla.fi](http://www.parla.fi)**

Manufacturer:

Timberwise Oy's  
Mikkeli factory Arinakatu 5  
FI-50170 Mikkeli, Finland  
Tel. +358 (0)2 763 6420  
[info@timberwise.fi](mailto:info@timberwise.fi)